# **Material Safety Data Sheet**



**SOLID POWER** 

# Section 1. Chemical product and company identification

Trade name : SOLID POWER

Product use : Machine Warewashing Detergent Supplier : Ecolab Inc. Institutional Division

370 N. Wabasha Street St. Paul, MN 55102 1-800-352-5326

Code : 949008

Date of issue : 15-August-2005

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

# Section 2. Composition, Information on Ingredients

<u>Name</u>	CAS number	% by weight
Sodium hydroxide	1310-73-2	35
triphosphoric acid, pentasodium salt	7758-29-4	18
Sodium carbonate	497-19-8	20 - 50

## Section 3. Hazards identification

Physical state : Solid. (Cast Solid)
Emergency : WARNING!

overview

Untreated contact may cause severe irritation or chemical burns.

CAUSES SEVERE EYE AND SKIN IRRITATION.

HARMFUL IF SWALLOWED.

Do not ingest. Do not get water inside container. Do not get in eyes, on skin or clothing. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

**Eyes**: Severely irritating to the eyes. Untreated contact may cause chemical burns.

**Skin**: Severely irritating to the skin. Untreated contact may cause severe irritation or chemical

burns.

**Inhalation**: No known significant effects or critical hazards.

**Ingestion**: Harmful if swallowed. May cause burns to mouth, throat and stomach.

See toxicological Information (section 11)

### Section 4. First aid measures

**Eye contact**: In case of contact, immediately flush eyes with cool running water. Remove contact lenses and

continue flushing with plenty of water for at least 15 minutes. Get medical attention

immediately.

**Skin contact**: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean

shoes before reuse. Get medical attention immediately.

**Inhalation**: If inhaled, remove to fresh air.

**Ingestion**: Rinse mouth; then drink one or two large glasses of water. Do not induce vomiting. Never give

anything by mouth to an unconscious person. Get medical attention immediately.

SOLID POWER Page: 2/4

## Section 5. Fire fighting measures

Flash point

: > 100°C

Fire fighting media and

instructions

: Use an extinguishing agent suitable for surrounding fires.

Dike area of fire to prevent product run-off.

No specific hazard.

for fire-fighters

Special protective equipment: Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure

mode.

#### Section 6. Accidental release measures

Personal precautions : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Prevent entry into sewers, water courses, basements or confined areas.

Environmental precautions Methods for

cleaning up

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and

sewers.

: If emergency personnel are unavailable vacuum or carefully scoop up spilled materials and place in an appropriate container for disposal. Avoid creating dusty conditions and prevent wind dispersal.

# Section 7. Handling and storage

Handling

: Do not ingest. Do not get in eyes, on skin or on clothing. Keep container closed. Use only with

adequate ventilation. Avoid breathing dust. Wash thoroughly after handling.

Storage

: Keep out of the reach of children. Do not get water inside container. Keep container tightly closed. Keep container in a cool, well-ventilated area.

Store between -10 and 50°C

# Section 8. Exposure Controls, Personal Protection

**Engineering** controls

: Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. When working with concentrate have eyewash available.

Personal protection

Eyes

: Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Hands

: Due to the form and packaging of the product, no protective equipment is needed under normal

use conditions.

Skin

: Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Respiratory

: No protective equipment is needed under normal use conditions.

Name

**Exposure limits** 

Sodium hydroxide

ACGIH TLV (United States, 9/2004). CEIL: 2 mg/m3 Form: All forms NIOSH REL (United States, 6/2001). CEIL: 2 mg/m3 Form: All forms OSHA PEL (United States, 6/1993). TWA: 2 mg/m<sup>3</sup> 8 hour(s). Form: All forms

# Section 9. Physical and chemical properties

: Solid. (Cast Solid) Physical state : Blue. (Light.) Color : Faint Odor Odor : 12.5 (1%) Hq

SOLID POWER Page: 3/4

# Section 10. Stability and reactivity

**Stability**: The product is stable.

**Reactivity**: Extremely reactive or incompatible with acids.

Highly reactive with metals. Reactive with organic materials.

# Section 11. Toxicological information

#### Potential acute health effects

**Eyes**: Severely irritating to the eyes. Untreated contact may cause chemical burns.

**Skin**: Severely irritating to the skin. Untreated contact may cause severe irritation or chemical

burns.

**Inhalation**: No known significant effects or critical hazards.

**Ingestion**: Harmful if swallowed. May cause burns to mouth, throat and stomach.

Chronic effects on : Contains material which causes damage to the following organs: lungs, upper respiratory

humans tract, skin, eye, lens or cornea.

# Section 12. Ecological information

Products of degradation : These products are carbon oxides (CO, CO<sub>2</sub>) and water, sulfur oxides (SO<sub>2</sub>, SO<sub>3</sub>

...), phosphates. Some metallic oxides.

# Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

# Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification	UN1759	Corrosive solids, n.o.s. (Sodium hydroxide)	8	III	Limited quantity Yes.  Special provisions 128, IB8, IP3

#### APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

## Section 15. Regulatory information

**HCS Classification** : Corrosive material

Target organ effects

**U.S. Federal regulations**: SARA 302/304/311/312 extremely hazardous substances: None.

SARA 302/304 emergency planning and notification: None.


**TSCA 8(b) inventory** : All materials are listed or exempt.

California prop. 65 : No products were found.

SOLID POWER Page: 4/4

### **Section 16. Other information**

Hazardous Material Information System (U.S.A.)



Date of issue : 15-August-2005.

Responsible name : Regulatory Affairs

Date of previous issue : 12-January-2005.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.